

Valve Regulated Lead Acid Battery

Maintenance-Free Sealed Lead Acid Battery

Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99%.



General Design for Standby Power Applications

【Design Life】

Up to 20 Years in Standby Service at 25°C
Eurobat (20°C) : >12 years very Long Life

【Operating Temperature Range】

Nominal Operating Temperature: 25°C (77°F)
Discharge : -15°C ~ 50°C (5°F ~ 122°F)
Charge : -15°C ~ 40°C (5°F ~ 104°F)
Storage : -15°C ~ 40°C (5°F ~ 104°F)

【Float Charging Voltage】

2.21 ~ 2.25 VDC/Unit at 25°C (77°F)

【Equalization Charging Voltage】

2.35 VDC/Unit at 25°C (77°F)


【Self Discharge】

Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F); Fully recharging is required before usage, and charged sooner if stored at higher temperature than 25°C (77°F).

Specification

Nominal Voltage	2V (single cells per unit)
Nominal Capacity	1000Ah@10HR-rate to 1.80V per cell @25°C (77°F)
Weight	Approx. 62.50 Kg (137.75 lbs)
Maximum Discharge Current	6000A (5sec)
Internal Resistance	Approx. 0.31 mΩ
Short Circuit Current	--
Maximum Charge Current	300A
Terminal types	I3 thread copper alloy terminal to accept M10 bolt
Terminal tightening torque	249±50 Kgf-cm / 216±43 Lbf-in / 24.4±4.9 N-m
Container Material	Flame Retardant Polypropylene (UL 94-VO)

Dimensions	Length (L)	303.0±3.0mm	11.93±0.12inch
	Width (W)	172.0±3.0mm	6.77±0.12inch
	Container Height (h)	497.0±3.0mm	19.57±0.12inch



Constant Current Discharge Characteristics Unit: A (25°C, 77°F)

F.V/Time	30MIN	60MIN	90MIN	2HR	2.5HR	3HR	5HR	6HR	8HR	10HR	20HR	24HR
1.60V	1087	678	509	417	356	313	205	175	137	112	56.0	46.7
1.67V	1042	662	498	407	348	306	200	172	134	110	55.0	45.8
1.70V	983	637	483	394	336	295	194	167	130	106	53.0	44.2
1.75V	901	602	459	377	322	283	188	162	127	104	52.0	43.3
1.80V	807	553	427	355	303	267	179	155	122	100	50.0	41.7
1.83V	714	503	394	331	284	250	169	146	117	95.0	47.5	39.6

Constant Power Discharge Characteristics Unit: W (25°C, 77°F)

F.V/Time	30MIN	60MIN	90MIN	2HR	2.5HR	3HR	5HR	6HR	8HR	10HR	20HR	24HR
1.60V	1707	1173	886	734	629	554	369	317	249	205	103	85.4
1.67V	1678	1152	872	724	621	548	364	315	247	204	102	85.0
1.70V	1642	1121	855	709	607	534	357	311	243	199	100	82.9
1.75V	1541	1066	817	682	584	515	348	303	239	197	98.5	82.1
1.80V	1420	990	769	650	557	491	335	291	231	190	95.0	79.2
1.83V	1307	920	725	619	532	470	323	279	225	183	91.5	76.3

Please refer to the official site for the latest rating confirmation.

Guang dong Xi shi bi Power Co.,Ltd

Tel: (总机) 020-84854238 Fax: 020-84854238

E-mail: csbusa@battery.com